

Trenchless plow Titan 786





Trenchless plow Titan 786

Technical Data

Engine	
Model	VOLVO, Diesel
Туре	TAD 1381 VE
Power	285 kW/388 PS bei 1900 rpm
Torque (max.)	1965 Nm bei 1200 rpm
Capacity of fuel tank	6801
Capacity of hydraulic tank	215
Electrical system	24 V

Traction drive	
Туре	hydrostatic individual
Travelling speed	0 - 5,8 km/h
Working speed	0 - 53 m/min
Drive control	infinitely variable, forward and reverse

Crawler unit	
Туре	Caterpillar D7, oscillating
Length	5604 mm
Track gauge	1950 mm
Track pads width	800 mm
Track pads type	In alternation 1-bar track pads/ 3-bar track pads
Track pads quantity	57, each side
Ground contact pressure	approx. 0,33 kg/cm²
Cornering (narrow)	swinging range of 8°, each side
Tilt control	tilting up to 10°, each side

Working performance (dependent on soil conditions)	
Plowing depth	max. 1,90 m
Plowing width (chute inside measurement)	100 mm NW Cable routing system on request up to 230 mm NW on request special chutes for cable laying for laying up to 16 cables or PE-pipes simultaneously
Floating position	adjustable

Dimensions (depending	Dimensions (depending on version)	
Width	approx. 2750 mm	
Length	approx. 10070 mm	
Height	approx. 3000 mm	
Weight	approx. 26800 kg	

Included in delivery	
automatic tilt control Heating	

Options
Cable routing system
→ Cable drum holder
>> Laser levelling automatic system
→ Additional cleats
→ Air conditioning
>>> Further engine performance classes
→ Camera system
Storage systems for accessories
→ Tool kit
Plowing depth indication via display
Centralized lubrication
→ Laser and GPS systems











Illustrations do not always show standard versions of machines.

Hüntelmann Drainage-Maschinen GmbH Große-Kreuz-Str. 5 · 49751 Werpeloh Germany

Tel.: +49 5952 9394 - 0 Fax: +49 5952 9394 - 10 info@huentelmann.com www.huentelmann.com

